

Technical Data Sheet



Product	FS 930 V FFP3 NR D
Filtering halfmask	
Approval and marking according to	EN 149:2001 + A1:2009
Level of Protection	FFP3 NR D
Performances	EN 149:2001 + A1:2009 requirements
Breathing Resistance	at 95 l/min 300 Pa
NaCl and paraffin oil penetration test	at 95 l/min
	sodium chloride [NaCl] 1%
	paraffin oil 1%
Dolomite clogging test	D marking
Material	
Filtering material	polypropylene
Head straps	braided elastomer
Nose foam	polyethylene
Nose clip	two metal-wires in plastic (polypropylene) cover
Valve	polypropylene
Attachments	polypropylene
Storage conditions & time	
Storage conditions & time	-20°C to + 40°C, < 90 % r. h. 3 years
Application	
The P3 class is designed for the protection of the respiratory tract against particulate aerosols, water-based aerosols (dust, smoke) and aerosols with liquid dispersed phase (mist), providing that the concentration of the dispersed phase does not exceed 30 x TLV. This class is used in high concentration of breathable dusts, used during welding and soldering, protects from dusts containing beryllium, antimony, arsenic, cadmium, cobalt, nickel, radium, strychnine, radioactive particles	

Respiratory protection is only effective if it is correctly selected, fitted and worn throughout the time when the wearer is exposed to hazards

NR - Non reusable (single shift only)

FILTER SERVICE SP. Z O.O., UL. SADOWA 7A, 95-100 ZGIERZ, POLAND
TEL: +48 427161518, FAX: +48 427171515, www.filter-service.eu., e-mail: filter@filter-service.eu